

*** HR FLATS**



Thick (In.)	Width (In.)	Lbs per Ft.
1/4	1/2	0.425
	3/4	0.638
	1	0.850
	1 1/4	1.060
	1 1/2	1.280
	1 3/4	1.490
	2	1.700
	2 1/4	1.910
	2 1/2	2.130
	2 3/4	2.340
	3	2.550
	3 1/2	2.980
	4	3.400
	4 1/2	3.830
	5	4.250
	6	5.100
	7	5.950
5/16	7 1/2	6.380
	8	6.800
	1	1.060
	1 1/4	1.330
	1 1/2	1.590
	2	2.130
	2 1/2	2.660
	3	3.160
	4	4.250
	5	5.310
5 1/2	5.840	
3/8	6	6.380
	7	7.440
	8	8.500
	3/4	0.956
	1	1.280
	1 1/4	1.590
	1 1/2	1.910
	1 3/4	2.230
	2	2.550
	2 1/2	3.190
3	3.830	
3 1/2	4.460	
4	5.100	
4 1/2	5.740	
5	6.380	

* Information provided for reference only. Not intended for engineering calculation. Please consult your engineer for product suitability for application. No warranty as to accuracy.

*** HR FLATS**



Thick (In.)	Width (In.)	Lbs per Ft.	
3/8	5 1/2	7.010	
	6	7.650	
	6 1/2	8.300	
	7	8.930	
	7 1/2	9.560	
	8	10.200	
	1/2	3/4	1.280
		1	1.700
1 1/4		2.130	
1 1/2		2.550	
1 3/4		2.980	
2		3.400	
2 1/4		3.830	
2 1/2		4.250	
3		5.100	
3 1/2		5.950	
4		6.800	
4 1/2		7.650	
4 3/4		8.080	
5		8.500	
5 1/2		9.350	
6		10.200	
7	11.900		
7 1/2	12.750		
8	13.600		
5/8	1 1/4	2.660	
	1 1/2	3.190	
	1 3/4	3.720	
	2	4.250	
	2 1/2	5.310	
	3	6.380	
	4	8.500	
	4 1/2	9.560	
	5	10.630	
	5 1/2	11.690	
	6	12.750	
	7	14.880	
8	17.000		
3/4	1	2.550	
	1 1/2	3.830	
	2	5.100	
	2 1/4	5.740	
	2 1/2	6.380	

* Information provided for reference only. Not intended for engineering calculation. Please consult your engineer for product suitability for application. No warranty as to accuracy.

*** HR FLATS**




Thick (In.)	Width (In.)	Lbs per Ft.	
3/4	3	7.650	
	3 1/2	8.930	
	4	10.200	
	4 1/2	11.480	
	5	12.750	
	5 1/2	14.030	
	6	15.300	
	7	17.850	
7/8	8	20.400	
	2	5.950	
	1	1 1/4	4.250
		1 1/2	5.100
		2	6.800
		2 1/2	8.500
		3	10.200
		3 1/2	11.900
4		13.600	
4 1/2		15.300	
1 1/8	5	17.000	
	5 1/2	18.700	
	6	20.400	
	7	23.800	
	8	27.200	
	8	30.600	
	1 1/4	2 1/2	10.630
		3	12.750
4		17.000	
6		25.500	
1 1/2	8	34.000	
	2	10.200	
	3	15.300	
	4	20.400	
	4 1/2	22.950	
	5	25.500	
1 3/4	6	30.600	
	8	40.800	
	3	17.850	
	4	23.800	
2	8	47.600	
	3	20.400	
	4	27.200	
	5	34.000	
2 1/2	8	54.400	
	3 1/2	29.750	
	5	42.500	
	6	51.000	


* Information provided for reference only. Not intended for engineering calculation. Please consult your engineer for product suitability for application. No warranty as to accuracy.

* HR ROUNDS		* HR SQUARES	
Dia. (In.)	Lbs. per Ft.	Size (In.)	Lbs. per Ft.
3/16	0.094	3/8	0.478
1/4	0.167	7/16	0.651
5/16	0.261	1/2	0.850
3/8	0.376	5/8	1.330
7/16	0.511	3/4	1.910
1/2	0.668	7/8	2.600
9/16	0.845	1.000	3.400
5/8	1.043	1-1/4	5.310
11/16	1.262	1-1/2	7.650
3/4	1.502	1-3/4	10.410
7/8	2.045	2.000	13.600
1	2.670	4.000	54.450
1-1/8	3.380		
1-1/4	4.172		
1-3/8	5.049		
1-1/2	6.008		
1-3/4	8.178		
2	10.681		
2-1/4	13.519		
2-1/2	16.690		
3	24.033		
3-1/2	32.712		
4	42.726		

Rounds



Squares



* UM Plates		
Thick (In.)	Width (In.)	Lbs per Ft.
9	5/16	9.58
	3/8	11.490
	1/2	15.310
	5/8	19.140
	3/4	22.970
10	1	30.630
	1/4	8.510
	5/16	10.640
	3/8	12.760
	1/2	17.020
	5/8	21.270
	3/4	25.520
	1	34.030
11	1-1/4	42.540
	1-1/2	51.050
	1/4	9.350
	5/16	11.700
	3/8	14.040
1/2	18.720	

* Information provided for reference only. Not intended for engineering calculation. Please consult your engineer for product suitability for application. No warranty as to accuracy.

*** UM Plates**



Thick (In.)	Width (In.)	Lbs per Ft.
11	5/8	23.400
	3/4	28.080
	1	37.440
12	1/4	10.210
	5/16	12.760
	3/8	15.310
	1/2	20.420
	5/8	25.520
	3/4	30.630
	1	40.840
13	1-1/4	51.050
	1-1/2	61.260
	3/8	16.590
14	1/2	22.130
	3/4	35.730
15	1	47.640
	3/8	19.140
18	3/8	22.970

* Information provided for reference only. Not intended for engineering calculation. Please consult your engineer for product suitability for application. No warranty as to accuracy.